

Bradnam's  
commercial  
Bi-fold Doors

The indoor answer to outdoor living...



# commercial Bi-fold Doors

## Performance Parameters

### Features and Benefits

- Ability to swing in, swing out, stack to one side or both sides
- Concealed locking system for a clean, contemporary look
- Access panel has a 4 point locking system for superior security
- Unique roller adjustment feature for smooth, trouble free operation
- Single entry door access available

Frame size	100mm
Maximum door height	3100mm
Maximum door width	8000mm
Maximum panel width	1000mm
Maximum panel weight	90kgs
Maximum water rating	300Pa
Maximum wind rating	6000 Pa ULS
Maximum glass thickness	13.52mm (single glazed) 26mm (IGUs)
Maximum bushfire attack level	BAL 40*

\* As per the deem to satisfy provisions outlined in AS3959

### The Bradnam's Difference



windows | doors | balustrade | insect & safety screens | showerscreens | mirrors & wardrobes



**Australian**  
Owned & Made

Bradnam's products are proudly made in Australia and designed specifically to meet all Australian conditions

**Note:** Products may be subject to local variation, regulatory requirements and confirmation of structural performance



**Bradnam's**  
windows & doors

For more information call Bradnam's on  
**1300 WINDOWS 1300 946369**  
or visit [bradnams.com.au](http://bradnams.com.au)